





# TECHNICAL DATA

<b>FABRICANT</b>	FOSHAN DOSUNTILE CO. LTD
<b>PRODUCT NAME SIZE AND MODEL</b>	<b>SAND</b> 600mm x 600mm Glazed matt tile
<b>TEST RESULTS</b>	The elements tested comply with the requirements of criteria GB/T3810.7-2016, BG/T3810.4-2016

TESTED ITEMS			TEST STANDARDS	RESULTS	
Surface abrasion resistance			GB/T3810.7-2016 GB/T3810.4-2016	2100 revolutions Class 4	
Breaking strength				1412N	
Modulus resistance				30.17 (MPa)	
Reference values for wear on glazed tiles	Level 2		GB/T3810.7-2016 GB/T3810.4-2016	Shoes for everyday use and, occasionally, a little dust and scratches on the floor. dust and scratches on the floor.	
	Level 3			Shoes suitable for normal use normal use on a clay floor with small stripes.	
	Level 4			Suitable for scratching dust, pedestrians walking on the floor	
	Level 5			Applicable to more hostile operating environments.	
Dynamic coefficient of friction			ANSI A326.3-2021	Wet DCOF Value (uD): 0.53	
Slip resistance			DIN 51130:2014	Oil-wetted inclined platform test. Average overall acceptance angle: 7.6°	R9